



<Speedway X2> <SAE 5W-40> <T1701 Ester Fully Synthetic Engine Oil>

DESCRIPTION

LOFGE <Speedway X2> <5W-40> T1701 Ester Fully Synthetic Engine Oil, the blending process adopt unique formulation technology of T1701 ester synthetic oil with special anti-wear and selected additives. It provides excellent protection in low-temperature pumping and fluidity, high-temperature stability and prevention of carbon deposition. Suitable for use under various environment and driving condition offers durable protection for modern high-performance engines.

Meets & Exceeds: ILSAC GF-5; API SN/CF; ACEA A3/B3, A3/B4.

Specification and Approval: ILSAC GF-5; API SN/CF; ACEA A3/B3, A3/B4; JASO SG+; MB229.2/MB229.3/229.5; VW502.00/505.00; GM LL-A/B-025; BMW LL-01; RN0700. RN0710.

APPLICATION

- ★ Racing and Rally Vehicle, Motorcycle, Off-road Vehicle and Road vehicle.
- ★ Suitable for turbocharging and natural aspirating multi-valve gasoline and diesel engine.
- ★ Can be applied to biodiesel and gasoline-ethanol blends as well.
- ★ Petrol & Diesel including DPF.

FEATURE

- The latest T1701 ester oil technology improves the strength and polarity of the oil film, also increases the negative charge of the oil film, and keeps the oil liquid permanently adsorbed on the metal friction surface, consummate get the experience the unmatched power and shielding abilities.
- Ultra-refined molecules, during cold engine start-up, most rapid participate in the circulation provides protection, start smooth and improve engine performance all-around.
- Extraordinary thermal stability and antioxidant properties, which extend the life of the engine.
- High viscosity index and abrasion resistance, excellent lubrication performance and reduced engine wear.
- The unique anti-friction additive can improve the cleaning of the piston also save fuel consumption and improve engine efficiency.
- It provides excellent protection in low-temperature pumping and fluidity, high-temperature stability and prevention of carbon deposition under harsh environment.
- Long-term alkalinity and prevent corrosion of machinery parts.
- The oil contains the trace of precious metals such as boron and molybdenum, which rapidly neutralise the total base value and maximise the performance of the oil film.

TYPICAL SPECIFICATION

LOFGE Speedway X2 SAE 5W-40	Units	Test Result
Appearance	-	Bright & Clear
Color	-	<3.0
Density (15°C)	Kg/m ³	851.9
Viscosity (40°C)	mm ² /s	78.37
Viscosity (100°C)	mm ² /s	14.23
Total Base Number	mgKOH/g	7.4
Viscosity Index	-	195
Flash Point COC	°C	248
Pour Point	°C	≤ -35

The typical specification mentioned represent mean values.